



TVP-1000
TVP-2000

The Preferred Choice

for Thermal Printers



TVP-2000



TVP-1000

Multi-Purpose Thermal Printing

Thermal Printer

TVP-1000 TVP-2000

Model Specification

MAIN FEATURES

	TVP-1000	TVP-2000
• Model	TVP-1000	TVP-2000
• Printing Method	Direct thermal	Direct thermal & thermal transfer
• Printing Resolution	203 dpi (8 dots/mm)	203 dpi (8 dots/mm)
• Max. Printing Speed	3.5 ips (89mm/s)	3 ips (76 mm/s)
• Max. Printing Length	45" (1143mm)	45" (1143mm)
• Max. Printing Width	2.2" (56mm)	4.13 (105mm)
• Fonts	5 alpha-numeric fonts from 0.49" - 0.23" height (1.25 - 6mm) All fonts are expandable up to 24 x 24 4 directions 0° - 270° rotation Soft fonts are downloadable	5 alpha-numeric fonts from 0.49" - 0.23" height (1.25 - 6mm) All fonts are expandable up to 24 x 24 4 directions 0° - 270° rotation Soft fonts are downloadable
• Barcodes	Code 39, Extended Code 39, Code 93, Code 128 (Subset A,B,C), Codabar, Interleave 2 of 5, EAN-8 2&5, EAN-13, EAN-128, UPC, UPC-A, E 2&5, Matrix 10	Code 39, Extended Code 39, Code 93, Code 128 (Subset A,B,C), Codabar, Interleave 2 of 5, EAN-8 2&5, EAN-13, EAN-128, UPC, UPC-A, E 2&5, Matrix 10
• 2D Barcodes	Maxicode, PDF-417, Datamatrix	Maxicode, PDF-417, Datamatrix
• Graphic	PCX bit map, GDI graphics	PCX bit map, GDI graphics
• Memory	512K standard	512K standard
• Interfaces	RS-232 serial, centronics	RS-232 serial, centronics
• Media	Roll-feed, die-cut, continuous, fan- fold, tags, tickets in thermal paper Width 1" - 2.36" (25 - 60mm) Length 0.4" - 45" (10 - 1143mm) Supply roll - Outer diameter 5" (127mm) - Inner diameter 1" (25mm)	Roll-feed, die-cut, continuous, fan- fold, tags, tickets in thermal paper Width 1" - 4.3" (25 - 110mm) Length 0.4" - 45" (10 - 1143mm)
• Ribbon	Nil	Wax, Wax/Resin, Resin Standard width - 1.3", 2.5", 3.3", 4.4" - 33mm, 64mm, 84mm, 109mm Ribbon roll - Outer diameter 1.4" (36mm) - Inner diameter 0.5" (12.5mm)
• Compact Size	5.3" (W) x 9.0" (D) x 6.4" (H) 134 (W) x 228 (D) x 163 (H) mm	7.3" (W) x 10.9" (D) x 6" (H) 186 (W) x 278 (D) x 153 (H) mm
• Weight	2.6 lbs (1.2 kg)	4.6 lbs (2.1 kg)
• Power Source	110 / 220 VAC +/- 10%, 50/60 Hz	110 / 220 VAC +/- 10%, 50/60 Hz
• Approvals	CE, UL, CUL, FCC, CLASS A	CE, UL, CUL, FCC, CLASS A
• Operation Environment	40° F - 100° F (4 - 38° C), 10 - 90% Non-condensing	40° F - 100° F (4 - 38° C), 10 - 90% Non-condensing
• Software	Label editing software - Digi X-bar & printer driver	Label editing software - Digi X-bar & printer driver

OPTIONS

- Cutter, dispenser kit, extension flash memory

* Specifications are subject to change without notice.

TERAOKA SEIKO CO., LTD

13 - 12 Kugahara 5-chome, Ohta-ku,
Tokyo 146-8580

Japan

TEL: +81-3-3752-2131

FAX: +81-3-3752-2801

EMAIL: info@hq.digi.co.jp

WEBSITE: <http://teraoka.digi.co.jp/index.nsf>

TERAOKA WEIGH-SYSTEM PTE LTD

4 Leng Kee Road #05-03/04/05

SIS Building Singapore 159088

TEL: (65) 472 2996

(65) 378 5388 (Sales)

FAX: (65) 472 2869

EMAIL: sales@teraoka.com.sg

WEBSITE: <http://www.teraoka.com.sg>